

4 by 2 HDMI Switcher with HEAC

CPRO-3D42S

NEW



This is a high performance HDMI™ Switcher with four HDMI inputs & two outputs HDMI™ Switcher, the output ports support Audio Return Channel (ARC) from a compatible TV/Display and HDMI Ethernet Channel (HEC) following the HDMI v1.4 specification.

- Simultaneously display a HDMI source on 2 TVs/ displays
- Connect internet capable devices through HEC to network routers/modems
- Connect network attached media streaming devices to compatible DTVs or Blu-ray players
- Showroom displays
- Educational demonstrations
- Commercial usage

| | |
|------------------------------|---|
| Frequency Bandwidth | 2.25 Gbps (Single Link) |
| Input Ports | 4 × HDMI (Female type) |
| Output Ports | 2 × HDMI (Female type) 2 × Ethernet 2 × ARC |
| Output Resolution | 480i ~1080p50/60, 1080p24, VGA~UXGA |
| HDMI Cable In | 1080p/8-bits or 12-bits (15m) |
| HDMI Cable Out | 1080p/8-bits or 12-bits (15m) |
| ESD Protection | Human Body model: ±8 kV (air-gap discharge) ±4 kV (contact discharge) |
| Power Supply | 5 V/2.6 A DC (US/EU standards, CE/FCC/UL certified) |
| Dimensions | 240 mm (W) × 113 mm (D) × 49 mm (H) |
| Weight | 810 g |
| Chassis Material | Metal |
| Silkscreen Color | Black |
| Operating Temperature | 0 °C~40 °C/ 32 °F~104 °F |
| Storage Temperature | -20 °C ~ 60 °C/-4 °F ~140 °F |
| Relative Humidity | 20~90 % RH (non-condensing) |
| Power Consumption | 4.2 W |

