

ETHERNET/USB to HDMI/VGA Display Converter

CDL-165ETHG



The device that can send audio/video signals from a Notebook/ PC over a local area network through regular Ethernet cables to a TV which can be used as the primary display. When a keyboard and mouse are plugged in, the device will let you to edit word processing documents and play your music/movies on a TV.



- Educational teaching
- Home entertainment
- Office network
- Home network

Video Resolution	Up to 1600x1200 /1920x1080 (wide)
Video Input	1xEthernet RJ-45 1xUSB 2.0
Network Protocol	TCP/IP
Video Output Ports	1xHDMI 1xD-Sub 15pin VGA
Extender Ports	2xUSB Hubs (A type)
Audio Output	1Vp-p 47 KΩ 3.5 mm Phone jack
OS Support	Windows XP SP2, Vista and 7
Power Supply	5 V DC/2.6 A (US/EU standards, CE/FCC/UL certified)
ESD Protection	Human body model: ±8 kV (air-gap discharge) ±4 kV (contact discharge)
Dimensions	119 mm (W)x88 mm (D)x25 mm (H)
Weight	120 g
Chassis Material	Plastic
Silkscreen Color	Black
Power Consumption	11 W
Operating Temperature	0 °C~40 °C / 32 °F~104 °F
Storage Temperature	-20 °C~60 °C / -4 °F~140 °F
Relative Humidity	20~90 % RH (non-condensing)

